

The Toro logo is displayed in white, bold, sans-serif capital letters inside a red rounded square.

ProStripe® 560

STRIPING MOWER

FEATURES

- Rear roller for that perfect, striped finish
- Superb cutting, collection, and smoothing in one pass
- Low cutting height for fine-turf applications
- Multi-speed traction gearbox for matching operator speed and specific turf conditions
- Blade Brake Clutch (BBC) improves operator comfort and efficiency
- Commercial-grade Kawasaki engine
- Zero-turn maneuverability with split rear roller helps eliminate turf damage on tight turns



MatchCut™ – Fine tune the cutting height with the MatchCut height of cut adjustment system. The system provides half-increment, 0.13" (3.25mm), settings and is ideal for use on highly manicured areas where multiple machines are used to provide an accurate, uniform height of cut across the entire area.



Groomer Brush Kit – Promotes healthier turf, while creating a cleaner cut and appearance by reducing lateral blade growth and loosening surface debris. Adjustable height and rake for precise tuning.

For a fairway finish.

The new Toro ProStripe 560 lets operators get the striping quality they need without sacrificing speed. The compact, lightweight design makes it easy to maneuver the ProStripe 560 in tight areas, so it's ideal for sports venues, municipalities, resorts and golf courses. It's also the fastest mower in its class*, helping to get the job done quicker. The ProStripe 560 provides both quality of cut, collection, and a clean striped finish in one efficient step.



Call your Toro distributor at 800-803-8676

* Based on average speed, measured on concrete.

©2021 The Toro Company. All rights reserved. Rev. 2/21



ProStripe® 560

The ProStripe 560 combines exceptional turf striping with the simplicity of a walk power mower. It is the ideal mower for striping smaller turf areas and can easily maneuver into tight locations.

PROSTRIPE 560, MODEL 02657*	
CUTTING WIDTH	22" (56 cm)
ENGINE	Kawasaki FJ180VKAI OHV 4-cycle, 179cc
TRACTION DRIVE	3-Speed Self Propelled
MOWING SPEED	1.9, 2.5, 3.1 mph (3.05, 4.02, 4.98 km/h)
DECK	Die cast corrosion resistant aluminum
HEIGHT OF CUT	7-position, 0.5"-2.6" (13-65 mm) in 0.29" (7.4 mm) increments (2 ranges of positions)
FUEL/CAPACITY	Gasoline/0.45 gal (1.7L)
WEIGHT	145 lbs (66 kg)
REAR ROLLER	Steel, Two-piece, ribbed for traction with composite end caps
AIR FILTER	Dual Element
BAG CAPACITY	21 gallon (80 liter)
BLADE ENGAGEMENT	Blade Brake Clutch (BBC)
WARRANTY	Two-year limited warranty. Refer to operator's manual for further details.



*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

